



G9226/7 Sprechstelle



Abb. Ähnlich

Funktion :

Ein Teilnehmer (1 Taste)
Electret-Schwanenhalsmikrofon (Lieferumfang)
Int. Expander / Begrenzer

Eingänge :

Impedanz : $\geq 4k\text{-Ohm}$ +6dBu Trafosymmetrisch
Max. Pegel : 15dBu

Ausgänge :

Impedanz : $< 40\text{-Ohm}$ +6dBu Trafosymmetrisch
Max. Pegel : 6dBu int. Limiter

Stromversorgung:


Ext. +24V (Lieferumfang)

Product Information

This document contains information for a MMB product.
MMB GmbH reserves the right to modify this product without notice.
Copyright © AUDIO INTEGRATED UNITS MMB GmbH 2015 (All Rights Reserved)



Technische Daten



G9227

G9226

G9226 / 27

RJ45 - Connector	Pin 1:	+ 4-Draht-Output
	Pin 2:	- 4-Draht-Output
	Pin 3:	+24V-Ext. Input
	Pin 4:	Cut (GPI)
	Pin 5:	DIM(GPO)
	Pin 6:	GND
	Pin 7:	+ 4-Draht-Input
	Pin 8:	- 4-Draht-Input

G9226

XLR - Connector Male	Pin 1 :	Sch.
	Pin 2 :	+ 4-Draht-Output
	Pin 3:	- 4-Draht-Output
XLR - Connector Female	Pin 1 :	Sch.
	Pin 2 :	+ 4-Draht-Input
	Pin 3:	- 4-Draht-Input

G9227

XLR - Connector 5p. Male KDO-1	Pin 1 :	Sch.
	Pin 2 :	+ 4-Draht-Ir KDO-1
	Pin 3:	- 4-Draht-In KDO-1
	Pin 4:	+ 4-Draht-OKDO-1
	Pin 5:	- 4-Draht-O _k KDO-1
XLR - Connector 5p. Male KDO-2	Pin 1 :	Sch.
	Pin 2 :	+ 4-Draht-Ir KDO-2
	Pin 3:	- 4-Draht-In KDO-2
	Pin 4:	+ 4-Draht-OKDO-2
	Pin 5:	- 4-Draht-O _k KDO-2